
SUPERLIGHTINGLED

LED Light Design Expert

Addressable LED sheet

Model Number: FLS-24V-5050-ARGBX192



SuperlightingLED is committed to provide high quality LED

- 1. The LED are packaged with pure gold wires and large-size chips.
- 2. Only one Bin LED is used for each order, and keep the same Bin LED in subsequent orders to ensure the consistency of the product.
- 3. The production process adopts high-temperature, lead-free SMT technology, the solder joints are smooth and full.
- 4. Use double-layer PCB to ensure stable electrical performance.
- 5. Use original authentic 3M tape, strong and long-lasting adhesion.
- 6. A variety of installation accessories are optional, flexible and convenient to use.
- 7. Different IP grade are available: IP20, IP54.
- 8. High light transmittance, environment friendly silicone material is used for waterproof product, colorless, odorless and anti-yellowing.



IP20 IP54

Product description

1. Dimensions: 490*245mm

2. Power: 42W/PCS

3. LED type: SMD5050

4. LED quantity: 192LED/32Pixels

5. LED color: Digital RGB

6. Cut length: 61.25x61.25mm

7. PCB material: double layer FPC

8. Life time: 36000hours

9. IP grade: IP20, IP54

Application


Home decoration lighting

Light box lighting


Stage lighting

Decoration of entertainment places

Product picture



Application scenarios











Technical parameters

LED Optical parameters	Electrical performance parameters	Other parameters
Red: 620-625nm	Voltage: DC24V	Storage temperature: -20~+60°C
Green: 520-525nm	Current: 1.75A	Working temperature: -20~+60°C
Blue: 460-465nm	Power: 42W/pcs	Life time: >50000 hours
Beam angle: 120°	Pixels: 32Pixels/pcs	Warranty: 3 years


Dimensions






Connection diagram


1. Power supply at the controller end




2. Power supply separately




Cutting method



Accessories




Connection piece*4




Connecting line*2



Screw*8



Screw shim*8



Anti-collision silicone particles*8