Manual Instruction

2. Parameters

Model No.: LM052 Input Voltage: DC12V~24V (5. 5*2. 1mm) ⊖-€--⊕ Output: 6A/Channel (Total Output Max. 15A) Working Temperature: -20~60°C



Smart Link&Unlink: We have 3 methods to Link and Unlink to APP. 1. Long press "SET" 3 seconds,the purple will blink 3 times,the device go into Smart Link/Unlink mode.

2. Use Linked 091 remote,long press the linked Zone ON button for 3 seconds, the purple light will blink 3 time, the device go into Smart Link and Unlink Mode

3. Switch ON and OFF 3 times(ON-OFF-ON-OFF-ON) within 10 seconds, the purple light will blink 3 time, the device go into Smart Link and Unlink Mode

Switching Output Mode: Short press "SET" button to switch the

Zigbee 3.0 5-in-LED Strip Controller

Please read the instructions carefully

WiFi wireless control

Smartphone APP control

Support third party

Support remote control

(control distance 30m)

2.4G wireless transmission

Device sharing

Group control

before using the controller.

1. Features

16 Millions of

Color temperature 2700K~6500K

Dim brightness /

Support music rhythm

Tap-to-Run & automation

Free screw wriein connecting to LED strip Free screw when

Auto-transmitting & Synchronization

Link/Unlink/Reset Button on the controller

Model No.: LM052

output mode; The indicating lamp flickering means switching successfully; Different colors ON correspond to different output mode; Details see below sheet. White Light Yellow Light Red Light Green Light Blue Light

first, then adjust the ouput mode Pilot lamp.


ON

ON Single Color Dual White Mode Mode RGB+CCT Mode RGB RGBW Suggestion: Complete the network distribution of the equipment

ON

3. Auto-synchronization function

Different controllers can work synchronously when they are started at different times, controlled by the same remote, under same dynamic mode and with same speed.




1. Indicating Auto-transmitting.

Controller will be auto-synchronizing in the same dynamic modes and within 30m controlling distance.


4. Auto-transmitting Diagram

One strip controller can transmit the signals from the remote control to another controller within 30m, as long as there is a strip controller within 30m, the remote control distance can be limitless



Connect to LED strip

Controller input voltage must be in accordance with the required voltage of LED Strips. Input voltage=Output Voltage









6. Remote Controller


Compatible with these remote controls (Purchased separately). For more details, pls read the remote instruction.







8. Free screw when connecting to LED strip







Zigbee 3.0 APP Control Instruction

1. Download and install [Tuya Smart] APP or [Smart Life] APP

Search for [Smart Life] in Apple or Google store or scan following QR code to download and install the app.

Please click " Register " button to create account while using it in the first time, Log in directly if you already had account





Connect to Smartphone

You must link the Tuva Zigbee 3.0 Gateway first to the smartphone. then add the zigbee controller to zigbee gateway for smartphone

(1). How to connect zigbee gateway to smartphone.(Note: All Tuya Zigbee 3.0 gateway in market can works on our Zigbee controller; Here we use our Zigbee 3.0 gateway for example).

First, Power the zigbee gateway, and long press the "SET" button until the red indicating lamp blinking.



Second, when the red indicating lamp blink, open the Smart Life APP,and press "Add Device".


It will discover the new device automatically, then Press "Add" to complete the linking



(2). Add the Zigbee controller to the linked zigbee gateway.

First, Power the controller, long press on "SET" button on the controller or switch the power 3 times(ON-OFF-ON), when the purple pilot lamp blink 3 time means the controller come into smart link mode. (Note: when the controller on the smart link mode, please finish the linking within 3 minutes, after 3 minutes, the controller will stop smart link mode, you need to do the above steps again).

Second, Press "Add new devices" on the APP, it will automatically find the zigbee device, then complete the linking. Added device will be displayed on the homepage after added successfully, then Click device you want to control to enter the control interface.



3. APP Control

(1). When you come into control page, Click **[dimmer]** on the bottom left corner, then click **[white]**, you can control the white light with color temperature, brightness, and save the white light you like.



Click [Color], you can control color change, brightness, saturation





Different Output support different Scene Sheet					
Modes	Single Color Output	Dual White Output	RGB Output	RGBW Output	RGBCCT Output
Color Change	×	×	√	√	√
CCT Adjust	×	√	√	×	√
Brightness Dimming	√	√	√	√	√

(3). Click [], you can come into Music rhythm control



(4). Click [] to come into More function including Schedule and Do Not Disturb.

Do not disturb function, pls read below pics carefully.





(5). Device name editing, Third-party Control, Device Sharing and Group Control.

(5.1)Click [on the top right corner of control page to come into extra function.

(5.2). Click icon under third-party control to view detailed

description of third-party control (5.3). Click [Share Device] to share the device to family and

Note: to share device, you need to create a home first, then

add members in to this home.Please read 6th instructions for how to make home management. (5.4). Click " Create Group " and follow APP prompt after setting is completed, the devices can be controlled by group.



(5). How to make Home Management for Device Sharing.

(6.1) Click [on the home page control interface, then click [Home Management] to enter Home management making.



(6.2) Click [Create a home] to complete home management, then you can add members on the home, and share device to your home number.



Note: Our Zigbee 3.0 controller also works on Philips Hue Bridge and Samsung Smartthings gateway for smartphone controlling.